PATEN

Attorney's Docket No.: U 012638-5

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Box Patent Application Assistant Commissioner for Patents Washington, D.C. 20231

NEW APPLICATION TRANSMITTAL

Transmitted herewith for filing is the patent application of Inventors:

- YOUNGDONG WU 1.
- HUIJIE ROBERT DENG 2.
- 3. FENG BAO

The Declaration must name all of the actual inventor(s). WARNING:

For (title):

REMOTE AUTHENTICATION BASED ON EXCHANGING SIGNALS REPRESENTING BIOMET-RICS INFORMATION

1. Type of Application

This new application is for a(n) (check one applicable item below):

- Original (nonprovisional)
- Design
- Plant

WARNING:

Do not use this transmittal for a completion in the U.S. of an International Application under 35 U.S.C. 371(c)(4) unless the International Application is being filed as a divisional, continuation or continuation-inpart application.

CERTIFICATION UNDER 37 CFR 1.10

I hereby certify that this New Application Transmittal and the documents referred to as enclosed therein are being deposited with the United States Postal Service on this date MARCH 3, 2000 in an envelope as "Express Mail Post Office to Addressee" Mailing Label Number EL386267783US addressed to the: Assistant Commissioner of Patents, Washington, D.C. 20231

IBIS CARRILLO

(type or print name of person mailing paper)

(Signature of person mailing paper)

NOTE: Each paper or fee referred to as enclosed herein has the number of the "Express Mail" mailing label placed thereon prior to mailing. 37 CFR 1.10(b).

WARNING:

Certificate of mailing (first class) or facsimile transmission procedures of 37 CFR 1.8 cannot be used to obtain a date of mailing or transmission for this correspondence.

(Application Transmittal [4-1]—page 1 of 7)

WARNING: Do not use this transmittal for the filing of a provisional application.

2. Benefit of Prior U.S. Application(s) (35 U.S.C. 119(e), 120, or 121)

NOTE: If the new application being transmitted is a divisional, continuation or a continuation-in-part of a parent case, or where the parent case is an International Application which designated the U.S., or benefit of a prior provisional application is claimed, then check the following item and complete and attach ADDED PAGES FOR NEW APPLICATION TRANSMITTAL WHERE BENEFIT OF PRIOR U.S. APPLICATION(S) CLAIMED.

WARNING: If an application claims the benefit of the filing date of an earlier filed application under 35 U.S.C. 120, 121 or 365(c), the 20-year term of that application will be based upon the filing date of the earliest U.S. application that the application makes reference to under 35 U.S.C. 120, 121 or 365(c). (35 U.S.C. 154(a)(2) does not take into account, for the determination of the patent term, any application on which priority is claimed under 35 U.S.C. 119, 365(a) or 365(b).) For a c-i-p application, applicant should review whether any claim in the patent that will issue is supported by an earlier application and, if not, the applicant should consider canceling the reference to the earlier filed application. The term of a patent is not based on a claim-by-claim approach. See Notice of April 14, 1995, 60 Fed. Reg. 20,195, at 20,205.

WARNING: When the last day of pendency of a provisional application falls on a Saturday, Sunday, or Federal holiday within the District of Columbia, any nonprovisional application claiming benefit of the provisional must be filed prior to the Saturday, Sunday or Federal holiday within the District of Columbia. See 37 C.F.R. § 1.78(a)(3).

☐ The new application being transmitted claims the benefit of prior U.S. application(s) and enclosed are ADDED PAGES FOR NEW APPLICATION TRANSMITTAL WHERE BENEFIT OF PRIOR U.S. APPLICATION(S) CLAIMED.

NOTE: If one of the following 3 items apply, then complete and attach ADDED PAGES FOR NEW APPLICATION TRANSMITTAL WHERE BENEFIT OF A PRIOR U.S. APPLICATION CLAIMED and a NOTIFICATION IN PARENT APPLICATION OF THE FILING OF THIS CONTINUATION APPLICATION.

☐ Divisional.

☐ Continuation.

☐ Continuation-in-Part (C-I-P).

Papers Enclosed That Are Required For Filing Date Under 37 CFR 1.53 (Regular) or 37 CFR 1.153 (Design) Application

- 27 Pages of specification
- 20 Pages of claims
- 1 Pages of Abstract
- 7 Sheets of drawing
 - ☑ formal
 - ☐ informal

WARNING:

DO NOT submit original drawings. A high quality copy of the drawings should be supplied when filing a patent application. The drawings that are submitted to the Office must be on strong, white, smooth, and non-shiny paper and meet the standards according to § 1.84. If corrections to the drawings are necessary, they should be made to the original drawing and a high-quality copy of the corrected original drawing then submitted to the Office. Only one copy is required or desired. Comments on proposed new 37 CFR 1.84. Notice of March 9, 1988 (1990 O.G. 57-62).

NOTE: "Identifying indicia, if provided, should include the application number or the title of the invention, inventor's name, docket number (if any), and the name and telephone number of a person to call if the Office is unable to match the drawings to the proper application. This information should be placed on the back of each sheet of drawing a minimum distance of 1.5 cm. (% inch) down from the top of the page." 37 C.F.R. 1.84(c).

(complete the following, if applicable)

		The ACC	enclosed drawing(s) are photograph(s), and there is also attached a "PETITION TO EPT PHOTOGRAPH(S) AS DRAWING(S)". 37 C.F.R. 1.84(b).					
4.	Ad	ditiona	I papers enclosed					
	abla	Preli	minary Amendment					
		Info	mation Disclosure Statement (37 CFR 1.98)					
		Form	PTO-1449					
		Citat	ions					
		Decl	aration of Biological Deposit					
		perta	nission of "Sequence Listing," computer readable copy and/or amendment ining thereto for biotechnology invention containing nucleotide and/or amino acid ence.					
		Auth	orization of Attorney(s) to Accept and Follow Instructions from Representative					
		Spec	ial Comments					
		Othe	r					
5.	Dec	laratio	n or oath					
	\square	Enclo	osed					
		exec	uted by <i>(check all applicable boxes)</i>					
		\square	inventors.					
			legal representative of inventors. 37 CFR 1.42 or 1.43					
			joint inventor or person showing a proprietary interest on behalf of inventor who refused to sign or cannot be reached.					
			This is the petition required by 37 CFR 1.47 and the statement required by 37 CFR 1.47 is also attached. <i>See item 13 below for fee.</i>					
		Not E	inclosed.					
WARA	IING:	availat Interna may be	the filing is a completion in the U.S. of an International Application but where a declaration is not the or where the completion of the U.S. application contains subject matter in addition to the tional Application the application may be treated as a continuation or continuation-in-part, as the case or utilizing ADDED PAGE FOR NEW APPLICATION TRANSMITTAL WHERE BENEFIT OF PRIOR U.S. CATION CLAIMED.					
			Application is made by a person authorized under 37 CFR 1.41(c) on behalf of all the above named inventors. (The declaration or oath, along with the surcharge required by 37 CFR 1.16(e) can be filed subsequently).					
NOTE:	It is i	mportan	t that all the correct inventor(s) are named for filing under 37 CFR 1.41(c) and 1.53(b).					
		-	Showing that the filing is authorized. (Not required unless called into question. 37 CFR 1.41(d).)					
6.	Inve	ntorsh	ip Statement					
WARN	ING:	If the n	amed inventors are each not the inventors of all the claims an explanation, including the ownership various claims at the time the last claimed invention was made, should be submitted.					
	The	inventorship for all the claims in this application are:						
		The same						
		Not the same. An explanation, including the ownership of the various claims at the time the last claimed invention was made,						

7.	Lang	Language								
NOTE:	Engli: 1.17	An application including a signed oath or declaration may be filed in a language other than English. A verified English translation of the non-English language application and the processing fee of \$130.00 required by 37 CFR 1.17(k) is required to be filed with the application or within such time as may be set by the Office. 37 CFR 1.52(d).								
NOTE:		A non-English oath or declaration in the form provided or approved by the PTO need not be translated. 37 CFI 1.69(b).								
	\square	Eng	lish							
		non	-English							
			the attached translation	is a verified translation. 37 C	FR 1.52(d).					
8.	Assignment									
	\square	An	assignment of the invent	ion to KENT RIDGE DIGITAL L	ABS.					
	☑ is attached. A separate ☑ "COVER SHEET FOR ASSIGNMENT (DOCUMENT) ACCOMPANYING NEW PATENT APPLICATION" or ☐ FORM PTO 1599 attached. □ FORM PTO 1599 □									
			will follow.							
NOTE:			nment is submitted with a new ignment." Notice of May 4, 19	application, send two separate letters 90 (1114 O.G. 77-78).	:—one for the application and one					
WARN	NG:	A ne	ewly executed "CERTIFICATE ication is filed by an assignee.	UNDER 37 CFR 3.73(b)" must be f Notice of April 30, 1993. 1150 O.G	iled when a continuation-in-part . 62-64.					
9.	Cert	ified	Сору							
	Cert	ified	copy of application							
			Country	Appln. No.	Filed					
		December 24, 1999								
		f	rom which priority is clai	med						
			is attached.							
		\square	will follow.							
NOTE:	The foreign application forming the basis for the claim for priority must be referred to in the oath or declaration 37 CFR 1.55(a) and 1.63.									
NOTE:	This item is for any foreign priority for which the application being filed directly relates. If any parent U.S. application or International Application from which this application claims benefit under 35 U.S.C. 120 is itselentitled to priority from a prior foreign application then complete item 18 on the ADDED PAGES FOR NEW APPLICATION TRANSMITTAL WHERE BENEFIT OF PRIOR U.S. APPLICATION(S) CLAIMED.									
10.	Fee	Calc	ulation (37 CFR 1.16)							
	Α.	☑	Regular Application							
				Claims as Filed						

Number Filed						V	lumber	Extra	a 	Rate	Basic Fee 37 CFR 1.16(a) \$690.00
Total Claims 74 - (37 CFR 1.16(c))						=	54	х	\$	18.00	972.00
-		nt Claims .16(b))		12	- 3	=	9	×	\$	78.00	702.00
Multiple dependent claim(s), if any (37 CFR 1.16(d))								+	\$	260.00	
	☐ Amendment cancelling					tra cla	aims en	close	ed.		
	\square	Amend	ment del	eting	g multi	ple-d	epende	ncies	ene	closed.	
	\square		extra cla								
NOTE:	mer	e fees for e nt, prior to ti ny notice of	he expirati	on of	the time	e perio	d set for	nust b respo	e pai nse b	id or the claims by the Patent an	cancelled by amend- d Trademark Office
							Filing	Fee	Calc	culation \$	690.00
В.			applicati 00 — 37		₹ 1.16	(f))	Filing	Fee	Calc	culation \$	
C.		Plant ap (\$480.0	plicatior 00 — 37		1.16	(g))	Filina	Fee (Calc	culation \$	
11.	Sm	all Entity	Statomo	nt(e)			9		-	Alation Y	
		Verified	Stateme	ent(s) that	this is 7 is(a	s a filin are) atta	g by iched	a sr d or	mall entity has been	
		Filing Fe	e Calcul	atior	า (50%	of A	A , B or	C ab	ove)	\$	
NOTE:	Any with	excess of ti in 2 months	he full fee of the da	paid v te of t	vill be re imely pa	efunde aymen	d if a ver t of a ful	ified s ' fee.	tater 37 C	ment and a refur CFR 1.28(a).	nd request are filed
12.		uest for l									ete, if applica-
		Please p	repare a en natio	n int nal e	ernatio xamin	onal-t ation	ype sea	arch meri	repo ts ta	ort for this ap akes place.	pplication at the
13.	Fee	Payment								μισο.	
		Not Encl									
			filing fe 37 CFR								rcharge required
		Engless	1								
	\square	Enclosed		r.							
		☑ bas	ic filing	тее						\$	690.00

			☑	Recording ass (\$40.00; 37 C SHEET FOR A APPLICATION	FR 1.21(F SSIGNME	h)) NT	(See attac ACCOMP	hed "CO\ ANYING	/ER NEW	,		
				Petition fee for or person on be refused to sign (\$130.00; 37)	ehalf of the or canno	he ot b	inventor w e reached.	rhere inve	ntors	\$		
				For processing a non-English I (\$130.00; 37	language.				ion ii	n \$		
				Processing and (\$130.00; 37				1))				
				Fee for interna (\$40.00; 37 C	tional-type FR 1.21(e	e se	earch repo	rt		\$		
N	OTE:	tailin CFR basic	g to co. 1.53 ai c filing t	1(I) establishes a fe mplete the applicat nd 1.78, indicate th fee must be paid or otification under §5	ion pursuant at in order t the process	t to o ob	37 CFR 1.53 btain the ben	'(d) and this efit of a pric	or U.S	ell a. . app	s the changes dication, either	to 37
							Total fees	enclosed	t	\$	690.00	
14		Met	hod o	f Payment of Fe	ees							
		\square	Chec	k in the amoun	t of \$	\$	690.00					
			Char	ge Account No.	. 12-0425	in	the amour	nt of		\$		
			A du	plicate of this t	ransmittal	is	attached.					
N	OTE:	Fees 1.22	should (b).	be itemized in such	a manner ti	hat i	it is clear for	which purp	ose tl	ne fe	es are paid. 37	7 CFR
15.	Aut	horiz	zation	to Charge Addi	itional Fee	s						
WARN	ING:	If no	o fees a	are to be paid on fill	ing, the follo	win	g items shou	ld <u>not</u> be co	omplei	ted.		
WARNI	NG:	Acc claii	urately m charg	count claims, espe ges are authorized.	cially multip	le d	ependent cla	ims, to avoi	id une	хрес	ted high charg	es, if extra
	☑	The pap	e Com per and	missioner is her d during the ent	eby autho tire pende	riz ncy	ed to charç / of this ap	ge the foll oplication	lowin to A	ig ad	dditional fee unt No. 12-	s by this -0425.
		☑	37 (CFR 1.16(a), (f)	or (g) (fili	ing	fees)					
			37 (CFR 1.16(b), (c)) and (d) (pre	sentation	of extra c	laim	s)		
	only by th	pe pa e PTC	id or th D in any	al fees for excess o ese claims cancelle notice of fee defic ees, except possibly	ed by amend. iency (37 CF	mer. R 1	nt prior to the .16(d)), it mi	e expiration aht be best	of the	time	e period set fo horize the PTC	r reenance
		37 late	CFR 1 r than	l.16(e) (surchar the filing date	ge for filir of the app	ng olic	the basic f ation)	iling fee	and/d	or de	eclaration o	n a date
	\square	37	CFR 1	.17 (application	processi	ng	fees)					
WARNII	NG:	shou 1.13	ild be m 16(a) is	FR 1.17(a), (b), (c) ade only with the kr to no avail <u>unless</u> 5,1985 (1060 O.G.	nowledge tha a request or	at: "	Submission of	of the approx	oriate i	exter	nsion fee under	7.37.C.F.R

37 CFR 1.18 (issue fee at or before mailing of Notice of Allowance, pursuant to 37 W

NOTE: Where an authorization to charge the issue fee to a deposit account has been filed before the mailing of a Notice of Allowance, the issue fee will be automatically charged to the deposit account at the time of mailing the notice of allowance. 37 CFR 1.311(b).

NOTE: 37 CFR 1.28(b) requires "Notification of any change in loss of entitlement to small entity status must be filed in the application ... prior to paying, or at the time of paying, ... issue fee". From the wording of 37 CFR 1.28(b): (a) notification of change of status must be made even if the fee is paid as "other than a small entity" and (b) no notification is required if the change is to another small entity.

16. Instructions As To Overpayment

 \mathbf{V} credit Account No. 12-0425

refund

> (Signature of attorney) WILLIAM R. EVANS LADAS & PARRY 26 WEST 61ST STREET

Tel. No. (212)708-1930

Reg. No. 25,858

NEW YORK, NEW YORK 10023

\square Incorporation by reference of added pages

(Check the following item if the application in this transmittal claims the benefit of prior U.S. application(s) (including an international application entering the U.S. stage as a continuation, divisional or C-I-P application) and complete and attach the ADDED PAGES FOR NEW APPLICATION TRANSMITTAL WHERE BENEFIT OF PRIOR U.S. APPLICATION(S) CLAIMED)

 Plus Added Pages for New Application	Transmittal Where	Benefit of Prior	·U.S. Applica-
tion(s) Claimed			• • •

Number of pages added ____ Plus Added Pages for Papers Referred to in Item 4 Above

Number of pages added ____

 \square Plus "Assignment Cover Letter Accompanying New Application"

Number of pages added 4

Statement Where No Further Pages Added

(If no further pages form a part of this Transmittal, then end this Transmittal with this page and check the following item:)

This transmittal ends with this page.

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application: YOUNGDONG WU, et al

For: REMOTE AUTHENTICATION BASED ON EXCHANGING SIGNALS

REPRESENTING BIOMETRICS INFORMATION

Attorney Docket No.: U 012638-5

Assistant Commissioner for Patents Washington, D.C. 20231

Sir:

PRELIMINARY AMENDMENT

Please amend the above application as follows:

IN THE CLAIMS

Claim 5, line 1, delete "or 3"

Claim 12, line 1, delete "or 10"

Claim 19, line 1, delete "or 17"

Respectfully submitted,

WILLIAM R. EVANS LADAS & PARRY 26 WEST 61ST STREET

NEW YORK, NEW YORK 10023 REG.NO.25858(212)708-1930

CERTIFICATE UNDER 37 1.10

I hereby certify that this paper is being deposited with the United States Postal Service on this date <u>MARCH 3, 2000</u> in an envelope as "EXPRESS MAIL POST OFFICE TO ADDRESS-EE" Mailing Label Number <u>EL386267783US</u> addressed to the: Commissioner of Patents and Trademarks, Washington, D.C. 20231

IBIS CARRILLO

(Type or print name of person mailing paper)

(Signature of person mailing paper)

NOTE: Each paper or fee referred to as enclosed herein has the number of the "EXPRESS MAIL" mailing label place thereon prior to mailing 37 CFR 1.16(b).

30

REMOTE AUTHENTICATION BASED ON EXCHANGING SIGNALS REPRESENTING BIOMETRICS INFORMATION

FIELD OF THE INVENTION

The present invention relates to the field of secure communications and in particular to techniques of remote authentication of, and secret key establishment between, communicating parties to protect or secure communications over insecure channels.

BACKGROUND

- Individuals or computer systems often need to have authenticated and confidential communications over an open channels, such as the Internet. While such secure communications may be achieved by physical means, it is more cost effective and flexible to use cryptographic means.
- To have secure communications using cryptographic means, parties need to first execute a protocol to authenticate each other and at the same time establish a mutually agreed conventional up on secret key, which is then used to encrypt subsequent communications between the parties. Conventional authentication and key exchange protocols normally require that, the parties either share a secret (e.g., a password) or know each other's public keys.

A cryptographic system, or cryptosystem, uses an encryption key to convert plaintext into ciphertext (an unintelligible or undecipherable form of the original information) and a decryption key to recover the plaintext from ciphertext. If the encryption key and the decryption key are identical, the cryptosystem is referred to as symmetric key cryptosystem. If the encryption and decryption keys are different and it is computationally infeasible to determine the decryption key from the encryption key, the cryptosystem is referred to as an asymmetric key cryptosystem or public key cryptosystem. In a public key cryptosystem, anyone can encrypt a message using a public encryption key. However, only the holder of a corresponding private decryption key can decrypt the ciphertext and recover the message.

EXPRESS MAIL LABEL NO.: EL386267783US

25

In a public key cryptosystem, it is often important to securely bind a public key with the legitimate user's ID. Such a binding can be achieved using public key certificates, which are digitally signed and issued by a certification authority.

- 5 Roughly speaking, a one-way hash function h() has the properties that:
 - 1) for any message m, the hash h(m) can be easily computed;
 - 2) given h(m), finding m is computationally infeasible; and
 - finding two messages that have the same hash is computationally infeasible.
- For more information on cryptosystems, digital signature schemes, public key certificates, and one-way hash functions, reference is made to A. Menezes, P. Oorschot, and S. Vanstone, <u>Handbook of Applied Cryptography</u>, CRC Press, pp. 425-488, pp. 559-561, and pp. 321-383 1996; and C. Kaufman, R. Perlman, and M. Speciner, <u>Network Security Private Communication in A Public World</u>, PTR
 Prentice Hall, Englewood Cliffs, NJ, pp. 152-158, pp. 177-204 and pp. 101-129 1995.

The UNIX (a trademark of Bell Laboratories) operating system provides a classical example of a password based authentication system. In UNIX, each user is provided with a unique login user name and is allowed to choose a secret password. The UNIX system maintains a password file containing the user name and a hash of the user's password computed using a one-way hash function with the user's password as input. When a UNIX user desires to access the UNIX system, the user keys in his or her user name and password to a terminal. The terminal computes the hash of the password and sends the hash along with the user name to the UNIX system. Because only the user knows the password, if the hash and user name match those in the password file, the user is considered authenticated.

The UNIX password system is simple to implement, but has a number of problems.

Firstly, it is vulnerable to a "replay" attack. That is an eavesdropper can intercept the

user name and the hash of the password, and replay them to the UNIX system.

Secondly, knowing the hash of a password, an eavesdropper can mount an off-line

dictionary attack. The person can guess a password, compute its hash, and see if the two hash values match. The person can then systematically try passwords, one at a time, until a match is found. Since people tend to choose easy to remember or "weak passwords", such an attack can be very effective. Thirdly, the UNIX system only authenticates the user, and no secret key is established to encrypt subsequent interactions between the user and the system.

A number of authentication and key establishment protocols have been proposed to improve upon the UNIX password protocol. Examples include:

1) R. Needham and M. Schroeder, "Using encryption for authentication in large networks of computers", *Communications of the ACM*, Vol. 21, December 1978, pp. 993-999;

2) D. Otway and O. Rees, "Efficient and timely authentication", *Operating Systems Review*, Vol. 21, No. 1, January 1987, pp. 8-10;

3) L. Gong, M. Lomas, R. Needham, and J. Saltzer, "Protecting poorly chosen secrets from guessing attacks", *IEEE Journal on Selected Areas of Communications*, Vol. 11, No. 5, June 1993, pp. 648-656; and 4) US Patent No. 5,440,635 issued to S. Bellovin and M. Merritt on

August 8, 1995.

20

25

15

5

A number of the conventional authentication protocols require that the parties share secret information (such as a password) or possess each other's public keys in advance. There are many potential difficulties for a human user to share secrets with a large number of remote parties. Firstly, it requires a secure secret distribution mechanism to be in place. Secondly and more importantly, human users are not good at remembering secrets of good quality, since such secrets look like random data. Knowing each other's public key in authenticated manners is also problematic in a distributed and open environment.

Without good authentication and encryption, voice-over-IP (the Internet protocol) can be eavesdropped without much difficulty. Pretty Good Privacy Phone or PGP fone (both are trademarks of Pretty Good Privacy Inc.) implements an authentication protocol based on exchange of voice signals and Diffie-Hellman key exchange protocol, P. Zimmermann, *PGPfone Owner's Manual, Version 1.0 beta 5*, 5 January 1996, http://web.mit.edu/network/pgpfone/manual.

5

10

15

20

25

30

Before proceeding with a discussion of the PGP fone authentication protocol, the Diffie-Hellman key exchange protocol, W. Diffie and M. Hellman, "New directions in cryptography", *IEEE Transactions on Information Theory*, Vol. IT-22, No. 6, pp. 644-654, November 1976 is reviewed. Diffie-Hellman key exchange allows two parties, without sharing keying material in advance, to agree to a secret key over an open channel, but without authentication. In Diffie-Hellman key exchange, two parties A and B agree on an appropriate prime p and a generator of Z^*_p , where $Z^*_p = \{x \mid 0 < x \le p-1\}$. Party A generates a random number x, 1 < x < p-1, and then computes and sends to Bob g^x modulo p. Party B generates a random number y, 1 < y < p-1, and then computes and sends to party A g^y modulo p.

Party A computes a shared key $k = (g^y)^x$ modulo p, and party B computes $k = (g^x)^y$ modulo p. The Diffie-Hellman protocol can be carried out in any group in which the discrete logarithm problem is difficult to solve. This protocol, however, is vulnerable to "man-in-the-middle" attacks. If a party C comes in the middle between parties A and B, when party A wishes to have a Diffie-Hellman exchange with party B, party C intercepts all the messages from A and B and enters the Diffie-Hellman exchange with A and B, respectively. As a result, C agrees a secret key with A and another secret key with B so that C can decrypt all the messages from A using the key shared with A and re-encrypt the messages using the key shared with B.

The PGPfone authentication protocol assumes that the two parties are familiar with each other's voice. The two parties first establish a shared value (e.g., $g^{xy} \mod p$) by performing a Diffie-Hellman exchange. The parties next compute the hash of the shared value. Each party then reads the first few bytes (in hexadecimal format or in English words. PGPfone; maintains a list that maps the 256 values of a byte to 256

English words) of the hash to each other. If the bytes at the two ends match and if the voice sounds like that of the claimed party, the parties are considered authentic.

However, if an attacker is able to collect sound samples of all the 256 words by, for example, eavesdropping on someone's phone calls, the attacker is able to impersonate the victim at will.

Thus, a need clearly exists for a method of remote authentication based on exchanging signals representing biometrics information and establishing a cryptographic key.

10 SUMMARY

5

15

In accordance with one aspect of the invention, a method of authenticating a remote party and establishing a cryptographic key for secure communications via an insecure communications channel. The method includes the steps of:

generating a first challenge signal of minimum duration T, where T is a fixed time interval;

generating a random number x, computing g^x modulo p, where g and p are numbers, deriving a key k_A from g^x modulo p, encrypting the first challenge signal with k_A and a symmetric key cryptosystem, and sending a first ciphertext to the remote party;

receiving a second ciphertext from the remote party, sending g^x modulo p to the remote party, and starting a clock;

receiving a third ciphertext and g^y modulo p from the remote party, stopping the clock, and computing an elapsed time interval of the clock;

deriving a key k_B from g^y modulo p, computing g^{xy} modulo p, deriving a key k_{AB} from g^{xy} modulo p, decrypting the second ciphertext with k_B to recover a second challenge signal from the remote party, decrypting the third ciphertext to recover a first response signal from the remote party;

verifying that the elapsed time of the clock is within a predetermined interval (TL_A, TU_A) , where TL_A and TU_A are positive numbers;

verifying that the second challenge signal is produced by the remote party;

30

25

producing a second response signal of minimum duration T, encrypting the second response signal with k_{AB} and sending a fourth ciphertext to the remote party;

verifying that the first response signal is a response produced by the remote party to the first challenge signal; and

generating a key k from gxy modulo p for secure communications with the remote party.

Correspondingly, an apparatus and a computer program product based on the foregoing method are also disclosed.

10

5

In accordance with another aspect of the invention, there is disclosed a method of authenticating a remote party and establishing a cryptographic key for secure communications via an insecure communications channel. The method includes the steps of:

15

receiving a first ciphertext from the remote party, generating a random number y, computing g^y modulo p, where g and p are numbers;

producing a first challenge signal of a minimum duration T, where T is a fixed time interval;

20

deriving a key k_B from g^y modulo p, encrypting the first challenge signal with k_B and a symmetric key cryptosystem, and sending a second ciphertext to the remote party;

receiving g^x modulo p from the remote party, deriving a key k_A from g^x modulo p, decrypting the first ciphertext to recover a second challenge signal from the remote party;

25

verifying that the second challenge signal is produced by the remote party, producing a first response signal of the minimum duration T;

computing g^{xy} modulo p, deriving a key k_{AB} from g^{xy} modulo p, encrypting the first response signal, sending a third ciphertext and gy modulo p to the remote party, and starting a clock;

receiving a fourth ciphertext, stopping the clock, computing the elapsed time of the clock, and decrypting the fourth ciphertext to recover a second response signal from the remote party;

verifying that the elapsed time of the clock is within a predetermined interval (TL_B, TU_B), where TL_B and TU_B are positive numbers;

verifying that the second response signal is a response produced by the remote party to the first challenge signal; and

generating a key k from g^{xy} modulo p for secure communications with the remote party.

10

15

5

Correspondingly, an apparatus and a computer program product based on the foregoing method are also disclosed.

In accordance with yet another aspect of the invention, there is disclosed a method of authenticating a remote party and establishing a cryptographic key for secure communications via an insecure communications channel. The method includes the steps of:

generating a first challenge signal of minimum duration T, where T is a fixed time interval;

generating a random number x, computing g^x modulo p, where g and p are numbers, deriving a key k_A from g^x modulo p, encrypting the first challenge signal with k_A and a symmetric key cryptosystem, and sending a first ciphertext to the remote party;

receiving a second ciphertext, sending g^x modulo p to the remote party, and starting a clock;

receiving g^y modulo p, computing a key k_B from g^y modulo p, decrypting the second ciphertext to recover a second challenge signal from the remote party;

verifying the second challenge statement to ensure that the second challenge statement is produced by the remote party, and producing a first response signal of minimum duration T;

30

25

computing g^{xy} modulo p, deriving a key k_{AB} from g^{xy} modulo p, encrypting the first response signal and sending a third ciphertext to the remote party;

receiving a fourth ciphertext from the remote party, stopping the clock, decrypting the fourth ciphertext with k_{AB} to recover a second response signal from the remote party;

verifying that the elapsed time of the clock is within a predetermined interval (tl_A, tu_A), where tl_A and tu_A are positive numbers;

verifying that the second response signal is a response produced by the remote party to the first challenge signal; and

generating a key k from g^{xy} modulo p for secure communications with the remote party.

Correspondingly, an apparatus and a computer program product based on the foregoing method are also disclosed.

15

25

5

In accordance with a further aspect of the invention, there is disclosed a method of authenticating a remote party and establishing a cryptographic key for secure communications via an insecure communications channel. The method includes the steps of:

receiving a first ciphertext from remote party, generating a random number y, and computing g^y modulo p, where g and p are numbers;

producing a first challenge signal of minimum duration T, where T is a fixed time interval;

deriving a key k_B from g^y modulo p, encrypting the first challenge signal with k_B and a symmetric key cryptosystem, and sending a second ciphertext;

receiving g^x modulo p, computing a key k_A from g^x modulo p, decrypting the first ciphertext to recover a second challenge signal from remote party, sending g^y to remote party and starting a clock;

verifying the second challenge statement to make sure that the second challenge statement is produced by the remote party, and then producing a first response signal of minimum duration T;

15

computing g^{xy} modulo p, deriving a key k_{AB} from g^{xy} modulo p, encrypting the first response signal and sending a third ciphertext to the remote party;

receiving a fourth ciphertext from the remote party, stopping the clock, decrypting the fourth ciphertext with k_{AB} to recover a second response signal from the remote party;

verifying that the elapsed time of the clock is within an interval (tl_B , tu_B), where tl_B and tu_B are positive numbers;

verifying that the second response signal a response produced by the remote party to the first challenge signal; and

generating a key k from g^{xy} modulo p for secure communications with the remote party.

Correspondingly, an apparatus and a computer program product based on the foregoing method are also disclosed.

BRIEF DESCRIPTION OF THE DRAWINGS

A small number of embodiments of the invention are described hereinafter with reference to the drawings, in which:

- Fig. 1 is a block diagram illustrating a communication system model between two remote individuals over an open transmission channel;
 - Fig. 2 is a flowchart depicting the operation of a first embodiment of the invention;
 - Fig. 3 is a flowchart showing the operation of a second embodiment of the invention;
 - Fig. 4 is a flowchart depicting the first scenario of a man-in-the-middle attack in the
- 25 first embodiment of Fig. 2;
 - Fig. 5 is a flowchart showing the second scenario of a man-in-the-middle attack in the first embodiment of the invention of Fig. 2;
 - Fig. 6 is a block diagram illustrating a communication device in accordance with the first embodiment of the invention; and
- Fig. 7 is a block diagram of a general-purpose computer with which the embodiments of the invention can be practised.

DETAILED DESCRIPTION

A method, an apparatus, and a computer program product for remote authentication based on exchanging signals representing biometrics information and establishing a cryptographic key are described. In the following description, numerous details are set forth including communications channels for example. It will be apparent to one skilled in the art, however, that the present invention may be practised without these specific details. In other instances, well-known features are not described in detail so as not to obscure the present invention.

10

20

25

5

The detailed description is organised as follows:

- 1. Notation and Definitions
- 2. Block Diagram of Communications Device
- 3. First Embodiment
- 4. Second Embodiment
 - 5. Security Considerations
 - 6. Computer Implementation

In the following description, components of the system are described as modules. A module, and in particular its functionality, can be implemented in either hardware or software. In the software sense, a module is a process, program, or portion thereof, that usually performs a particular function or related functions. In the hardware sense, a module is a functional hardware unit designed for use with other components or modules. For example, a module may be implemented using discrete electronic components, or it can form a portion of an entire electronic circuit such as an Application Specific Integrated Circuit (ASIC). Numerous other possibilities exist. Those skilled in the art will appreciate that the system can also be implemented as a combination of hardware and software modules.

30 <u>1. Notation and Definitions</u>

The following notation is used throughout:

	A, B:	Parties (Alice and Bob, respectively) that seek to have
		secure communications;
	e(k, m):	Encrypted message containing original message m and
		a key k using a symmetric key cryptosystem;
5	d(k, c):	Decrypted message containing a ciphertext c and the
		key k using a symmetric key cryptosystem;
	C_X :	An acoustic wave or digital representation of a
		challenge statement spoken by a party X (either A or
		B); whether C _X is an acoustic wave or a digital
10		representation should be clear to those skilled in the art
		from the discussion context;
	R_Y :	An acoustic wave or digital representation of a response
		statement spoken by a party Y in reply to C _X ; whether
		R _Y is an acoustic wave or a digital representation
15		should be clear to those skilled in the art from the
		discussion context;
	$ C_X $:	the time duration of C_X ;
	$ R_Y $:	the time duration of R _Y ; and
	T:	A required minimum time duration of any statement
20		spoken by a party.

In the following description, "secure communications" means communications that are authenticated or confidential.

Fig. 1 illustrates a general model 100 of communications between two remote

25 individuals. In this model 100, Alice 110 and Bob 150 are two individuals, who are
familiar with each other's biometrics characteristics (without loss of generality, voice
signals are used hereinafter) and wish to have a secure communication. The
transmission channel 130 represents the means, and more specifically the media,
through which communication messages are exchanged between the communication

30 devices 120, 140. The transmission channel 130 includes, but is not limited to, any
communications means or media such as computer networks, public telephone

10

switching networks, and radio links. Alice 110 and Bob 150 communicate with each other by interfacing through communication devices (A) 120 and (B) 140, respectively. Devices (A, B) 120, 140 have appropriate speech signal processing capabilities (such as speech encoding and decoding). The devices 120, 140 accept audio input, either directly or indirectly, from Alice 110 and Bob 140, respectively, and output the other party's received audio signal.

In the embodiments of the invention, devices (A, B) 120, 140 each exchange signals using a Diffie-Hellman key exchange system and a symmetric key cryptosystem. For the purposes of illustration only, both devices (A, B) 120, 140 are assumed to have access to a common set of Diffie-Hellman parameters, g and p, which may be distributed either off-line or on-line.

The minimum duration of any statement spoken by a party 110, 150 is required to be

T, where T is either pre-fixed or agreed upon by Alice 110 and Bob 150. For security reasons, T should be much longer than the channel round-trip delay and the processing delay of each device 120, 140. For example, T may be in the range of tens of seconds to several minutes, while channel round-trip delay and processing delays are normally less than one second. To keep notation compact, only residues modulo are used hereinafter: that is, g^x modulo p, g^y modulo p, and g^{xy} modulo p are written simply as g^x, g^y, and g^{xy}, respectively. In addition, while not mentioned explicitly, devices (A and B) 110, 150 are assumed to perform audio encoding/decoding and audio compression/decompression operations, whenever necessary.

In the embodiments of the invention, the communicating parties are assumed to be familiar with each other's voice (biometrics characteristics in general) and able to recognise each other by listening to each other's speech. This is a reasonable requirement, since there are generally no confidential topics between two strangers without the involvement of a trusted third party. In the embodiments, party 110

(Alice) starts a session with party 150 (Bob) by speaking a challenge statement such

as:

"This is Alice! The time is 21 minutes passed 9AM. How was your mid-term examination, Bob?".

Upon hearing Alice's message, party 150 (Bob) is expected to speak a response statement like:

"Hi, Alice! Bob's here. My mid-term exam was not very good. But thank God, it is over!".

In the embodiments, Alice is assumed to be able to distinguish whether the stated response is in Bob's voice and whether the stated response corresponds to her challenge statement in the first place. Furthermore, it is assumed that it is difficult for an attacker to mimic a target party's voice to produce a meaningful response statement in real-time.

15 <u>2. Block Diagram of Communications Device</u>

Fig. 6 is a block diagram of a communication device 600 in accordance with the embodiments of the invention. The communications device 600 includes a speech encoding/decoding module 632, a control module 636, an encryption/decryption module 640, a key generator 650, a Diffie Hellman key exchange system 660, a timer module 670, an input/output (I/O) module 680 for transmitting and receiving data via the communications channel 610, and a memory 682. Optionally, the device 600 also includes a transducer module 630 and an audio compression/decompression module 634.

The control module 636 controls the components of the device 600 via signals 690A – 690I. The transducer module 630 converts audio 620 into audio signals and vice versa. Operation of the transducer module 630 can be controlled by the control module 636 via a control signal(s) 690A. In turn, the transducer 630 is coupled bidirectionally with the speech encoding/decoding module 632. This module 632 speech encodes and decodes data and is controlled by the control module 636 via the signal(s) 690B. Optionally, the speech encoding/decoding module 632 is coupled

bidirectionally to an audio compression/decompression module 634. Otherwise, the module 632 can be directly coupled to an encryption/decryption module 640. The control module 636 is coupled to the audio compression/decompression module 634 via the control signal 690C.

5

The encryption/decryption module 640 is optionally coupled to the audio compression/decompression module 634 and is coupled to the control module 636 via a control signal(s) 690D. The encryption/decryption module 640 is also coupled to memory 682, Diffie Hellman key exchange system 660, timer module 670, and the I/O module 680 by bus 692. The key generator 650 is coupled between the Diffie Hellman key exchange system 660 and the encryption/decryption module 640. The key generator 650 produces a key k from a code G^Z and is coupled to the control module 636 via a control signal(s) 690E. The memory 682 is coupled to the control module 636 via a control signal(s) 690G.

15

20

10

The Diffie Hellman key exchange system 660 has as inputs code G, prime number P, random value X, and a control signal(s) 690F from control module 636. The timer module 670 has an interrupt (INT) output to the I/O module 680 that allows the timer module 670 to interrupt transmission/reception of data via the I/O module 680. The timer module 670 is coupled to the control module 636 via a control signal 690I. The I/O module 680 is coupled to the control module 636 by control signal(s) 690H. Operation of the communication device 600 is described hereinafter with reference to the first and second embodiments.

u: in

25

30

The embodiments of the invention advantageously employ mechanisms that enable users to authenticate each other and have secure communications over open or insecure channels by using a different technique. More particularly, users are not required to share or remember any secret key or password, or possess each other's public keys in advance. Authentication and key establishment are achieved by exchanging signals representing a remote party's biometrics information. In this connection, the embodiments of the invention utilize a cryptographic one-way hash

function. The embodiments concentrate on authenticating remote human users based on the interaction of signals representing a remote party's biometrics information (such as acoustics waves). Parties are assumed to be able to identify each other based on the exchanged biometrics signals. There is no need for the parties to share any secret key, or know each other's public key in advance. The embodiments of the invention can be advantageously employed in applications such as Internet telephoning or voice-over-IP (Internet Protocol).

3. First Embodiment

- Fig. 2 is a flowchart illustrating the method of secure communications according to the first embodiment of the invention. The flowchart is organised in columns in the following order: Alice 110, device (A) 120, device (B) 140, and Bob 150. In step 210, Alice 110 speaks a challenge statement C_A, which is input to Device A (shown as device 600 in Fig. 6). Preferably, the challenge statement C_A contains some
 "freshness" elements, such as the date and time, and news headlines of the day. In step 212, Device A generates a random number x and computes g^x. Device A then preferably computes a key k_A from code g^x using the key generator. Next, Device A encrypts the challenge statement C_A with key k_A using the key generator and sends the ciphertext, referred to as Message A1:
- e(k_A, C_A),

 preferably together with Alice's identity to Device B over the transmission channel
 610.
- In step 214, Device B receives the Message A1 and prompts Bob to speak a challenge statement C_B in step 216. In step 218, Device B generates a random number y, computes g^y and preferably a key k_B from the code g^y for a symmetric key cryptosystem. Device B then encrypts C_B and transmits the ciphertext, referred to as Message A2:

 $e(k_B, C_B),$

30 preferably together with Bob's identity to Device A.

In step 220, Device A receives the Message A2. In step 222, Device A sends to Device B the code, referred to as Message A3:

g^x,

5

10

15

30

and starts a clock or timer to measure the time interval for a response. In step 224, after receiving code g^x , Device B computes the key k_A from the code g^x and decrypts the ciphertext received in Message A1 to recover the challenge statement C_A . Device B then plays back the challenge statement C_A to Bob. In step 226, Bob listens to the challenge statement C_A and verifies that the voice belongs to Alice. If the verification fails, Bob terminates the session. Otherwise, in step 228, Bob speaks a response statement R_B in reply to the challenge statement C_A (e.g., by iterating C_A in his own voice).

In step 230, Device B computes the code $(g^x)^y = g^{xy}$ and a key k_{AB} from g^{xy} in well-known fashion for the symmetric key cryptosystem, and encrypts R_B with k_{AB} and the symmetric key cryptosystem to obtain $e(k_{AB}, R_B)$. In step 232, Device B sends, as Message A4, the following:

$$g^y$$
, $e(k_{AB}, R_B)$,

to Device A and then starts its clock.

In step 234, upon receipt of Message A4, Device A first stops its clock started in step 222. Time t_A is the elapsed time of the clock. Device A then computes the code (g^y)^x = g^{yx}, the key k_{AB} from code g^{yx}, and the key k_B from the code g^y. Device A then decrypts e(k_B, C_B) with the key k_B and e(k_{AB}, R_B) with key k_{AB} to recover the challenge statement C_B and the response R_B, respectively. |C_A| is the duration of the challenge statement C_A, and |R_B| is the duration of the response R_B. It will be readily apparent to those skilled in the art how to obtain the duration of an audio signal. Let TL_A = |C_A| + |R_B|. Further, in step 230, Device A checks the elapsed time t_A to see if:

$$t_{A} \in (TL_{A}, TU_{A}), \tag{1}$$

where TU_A can be taken advantageously as $T + TL_A$ if the channel round trip delay and processing delay in Devices A and B 120, 140 are negligible compared with T. Such delays can be easily incorporated into Equation (1) by those skilled in the art. If

 $t_A \in (TL_A, TU_A)$ is not true, Device A terminates the session. Otherwise, in step 236, Alice listens and verifies the challenge statement C_B .

If Alice recognises that the challenge statement C_B is not Bob's voice, Alice terminates the session. Otherwise, in step 238, Alice speaks a response statement R_A (e.g., by iterating C_B in her own voice) in reply to the challenge statement C_B . In step 240, Device A encrypts the response statement R_A with the key k_{AB} and sends to Device B the ciphertext, as Message A5:

 $e(k_{AB}, R_A)$.

In step 248, following step 238, Alice listens and verifies the response statement R_B. If the response statement R_B is not either a response to the challenge statement C_A or in Bob's voice, Alice stops the session. If Alice is sure that the response statement R_B is a reply to the challenge statement C_A in Bob's voice, she begins communicating in step 250.

15

20

25

5

Next, from step 240 in step 242, upon receipt of Message A5, Device B stops its clock or timer. The time t_B is the elapsed time of the clock. Also, Device B decrypts $e(k_{AB}, R_A)$ with the key k_{AB} to obtain the response statement R_A . Let $|C_B|$ denotes the playback duration of C_B and $|R_A|$ the playback duration of R_A . Let $TL_B = |C_B| + |R_A|$. In step 242, Device B checks the elapsed time to see if:

$$t_{\rm B} \in (TL_{\rm B}, TU_{\rm B}),$$
 (2)

where TU_B can be taken advantageously as $T + TL_B$ if the channel round trip delay and processing delay at Devices A and B are negligible in comparison with T. If Equation (2) is not satisfied, Device B terminates the session. Otherwise, Device B plays back the response statement R_A to Bob. In step 244, Bob listens and verifies the response statement R_A . If Bob recognises that R_A is a reply to the challenge statement C_B in Alice's voice, Bob can be confident that he is communicating with Alice and he can proceed to step 246. Otherwise, Bob stops the session.

In steps 250 and 246, respectively, Bob and Alice preferably communicate with each other. In step 252, Device A encrypts messages from Alice and decrypts messages

from Bob with a key derived from g^{xy}, preferably using another symmetric key cryptosystem. Similarly, in step 256, Device B likewise encrypts messages from Bob and decrypts message from Alice with a key derived from g^{xy} in the same way as Device A and with the same symmetric key cryptosystem as used by Device A.

5

10

15

4. Second Embodiment

Fig. 3 is a flowchart illustrating a method of secure communications according to the second embodiment of the invention. In step 310, Alice starts the session by speaking a challenge statement C_A . In step 312, Device A generates a random value x, computes a code g^x and a key k_A from g^x for a symmetric key cryptosystem, encrypts the challenge statement C_A with k_A and sends to B the ciphertext, as Message B1:

 $e(k_A, C_A)$.

In step 314, Device B receives Message B1. Next, in step 316, Device B prompts Bob to speak a challenge statement C_B in step 318. In step 316, Device B then generates a random number y, computes code g^y and a key k_B from g^y for a symmetric key cryptosystem, encrypts C_B with k_B and sends to Alice the ciphertext, as message B2:

 $e(k_B, C_B)$.

20 In step 320, Device A receives Message B2. Next, in step 322, Device A sends to Bob, as Message B3:

g^x,

and starts a clock.

In step 324, upon receipt of the Message B3, Device B computes a key k_A from code g^x , decrypts $e(k_A, C_A)$ to recover C_A , sends to Alice as Message B4:

g^y,

and starts a clock. Device B then outputs the challenge statement C_A to Bob. In step 326, Bob listens and verifies whether the challenge statement C_A is in Alice's voice.

30 Bob terminates the process if he has doubts on the originality of the challenge statement C_A. When the challenge statement C_A is verified successfully by Bob, in

step 328, Bob speaks a response statement R_B in reply to the challenge statement C_A . In step 330, Device B computes code g^{xy} and a key k_{AB} from g^{xy} , encrypts R_B and sends to Alice the ciphertext, as Message B5: $e(k_{AB}, R_B)$.

5

10

15

20

On the other hand, Message B4 is received by Device A in step 332. Device A computes k_B from g^y , decrypts $e(k_B, C_B)$ to recover C_B . Alice listens and verifies C_B in step 334. Alice stops the process if she believes that C_B is not in Bob's voice; otherwise, she speaks a response statement R_A in reply to C_B in step 336. In step 338, Device A computes g^{yx} and k_{AB} from g^{yx} , encrypts R_A and sends to Bob the ciphertext, as Message B6: $e(k_{AB}, R_A)$.

In step 340, Device A receives Message B5. Device A also stops the clock, decrypts $e(k_{AB}, R_B)$ to recover the response statement R_B and checks to see if the elapsed time of the clock T_A satisfies the following:

$$T_A \in (tl_A, tu_A), \tag{3}$$

where preferably $tl_A = |C_A| + |R_B|$ and $tu_A = tl_A + T$. Device A terminates the session if Equation (3) is not satisfied. Otherwise, Device A outputs the response statement R_B to Alice. In step 342, Alice listens and verifies the response statement R_B . Alice stops the session if she is not convinced that the response statement R_B is Bob's response to the challenge statement C_A . Otherwise, in step 344, Alice starts communications with Bob.

In step 348, upon receipt of the Message B6, Device B stops its clock, decrypts e(k_{AB}, R_A) to recover R_A. Device B, then checks to see if the elapsed time of its clock satisfies the following:

$$T_{B} \in (tl_{B}, tu_{B}) \tag{4}$$

where preferably $tl_B = |C_B| + |R_A|$ and $tu_B = tl_B + T$. Device B terminates the session if Equation (4) is not satisfied. Otherwise, Device B outputs the response statement R_A to Bob. In step 350, Bob listens and verifies R_A . Bob stops the session if he is not

convinced that the response statement R_A is Alice's response to C_B . Otherwise, in step 352, he starts communications with Alice.

With successful authentication of both Alice and Bob, Devices A and B, derive a key from g^{xy} and use the key to encrypt and decrypt messages between Alice and Bob in steps 346 and 354, respectively, using communications obtained in steps 344 and 352.

5. Security Considerations

Symmetric key cryptosystems are used in the embodiments to encrypt challenge signals and response signals. It is important that all encryptions resist data modification (such as cut and paste) attacks.

The symmetric key cryptosystem used to encrypt challenge and response signals can be replaced by a cryptographic commitment function. Such a commitment function has the following properties:

- no one can modify the contents of the commitment without being detected; and
- 2) no one can get any information about its contents unless the committing party discloses the information.

20

25

30

15

One way to form a commitment function is using a cryptographic one-way hash function h(). To commit to an item I, the committing party computes the commitment $h(k \parallel I)$, where k is a secret key and $k \parallel I$ is the concatenation of k and I. To verify the commitment, the verifying party must have k and I, compute h $(k \parallel I)$ and compare h $(k \parallel I)$ with the commitment.

Checking the lengths of the elapsed time intervals of the clocks in both illustrative embodiments is very important in detecting any man-in-the-middle attacks. This is illustrated using the two attacking scenarios respectively, in relation to the first embodiment of Fig. 2. A similar analysis can be done for the second embodiment. In the following descriptions, the term "Alice" is used to refer to both the user Alice and

Device A. Similarly, the term "Bob" is used to denote both the user Bob and Device B.

Fig. 4 depicts a scenario where Alice attempts to set up a communications session with Bob and where Clark performs a man-in-the-middle attempt to impersonate Bob to Alice. The flow diagram is accordingly organised into three columns: Alice, Clark and Bob. In step 410, Alice starts a session by generating a random number x, computing g^x , speaking a challenge statement C_A , computing k_A from g^x , encrypting k_A with k_A , and sending the ciphertext $e(k_A, C_A)$ to Bob.

10

15

5

In step 412, the ciphertext is intercepted by Clark. Clark generates a number z, computes g^z and a key k_C from g^z , encrypts an old challenge statement C'_B from Bob, and sends the ciphertext $e(k_C, C'_B)$ to Alice. In step 414, Alice receives the ciphertext, replies with g^x and starts a clock. The code g^x is again intercepted by Clark at step 416. In step 416, Clark derives the key k_A from g^x and decrypts $e(k_A, C_A)$ to recover C_A . Clark cannot mimic Bob's voice to produce a meaningful response statement R_B , so Clark impersonates Alice and starts a new session with Bob by sending Bob $e(k_C, C_A)$.

20

In step 418, upon receipt of $e(k_C, C_A)$, Bob generates a random value y, and computes code g^y and a key k_B . Bob then speaks a challenge statement C_B , encrypts the challenge statement using key k_B , and sends the ciphertext $e(k_B, C_B)$ to Alice. Clark intercepts the ciphertext in step 420. To continue impersonating Alice, Clark sends g^z to Bob. In step 422, Bob computes key k_C from g^z , decrypts $e(k_C, C_A)$, and listens C_A , which was indeed spoken by Alice. Bob speaks a response statement R_B , computes a key k_{BC} from g^{zy} , encrypts R_B with k_{BC} , and transmits g^y and the ciphertext $e(k_{BC}, R_B)$. In step 424, Clark again intercepts the ciphertext, computes the key k_{BC} from g^{yz} , and decrypts $e(k_{BC}, R_B)$. Now Clark gets R_B . Clark then computes k_{AC} from g^{xz} , encrypts R_B with k_{AC} , and sends the ciphertext $e(k_{AC}, R_B)$ to Alice.

25

In step 426, Alice stops the clock, decrypts $e(k_C, C'_B)$ and $e(k_{AC}, R_B)$ to recover C'_B and R_B , respectively. Alice also listens and verifies that C'_B is in Bob's voice. Alice then speaks and encrypts a response statement R_A , and sends the ciphertext $e(k_{AC}, R_A)$.

Next, in step 428, Alice listens and verifies the response statement R_B . Since R_B is indeed a response to C_A from Bob, Alice is fooled into believing Clark is Bob. However, the embodiments of the invention prevent this from happening by checking the clock's elapsed time t_A against the interval (TL_A, TU_A) per Equation (1), where $TL_A = |C_A| + |R_B|$, and $TU_A = TL_A + T$.

10

15

To appreciate the rationale behind Equation (1), without the man-in-the-middle attack by Clark, $t_A = |C_A| + |R_B| + \Delta_{A1}$, where Δ_{A1} is the delay due to processing, transmission, and a pause interval introduced by Bob after listening to the challenge statement C_A , but before speaking the response statement R_B . However, with the manin-the-middle attack shown in Fig. 4, $t_A = |C_A| + |R_B| + |C_B| + \Delta_{A2}$, where Δ_{A2} is a delay similar to Δ_{A1} . Since it is required that $T >> \Delta_{A1}$ and Δ_{A2} and that $|C_B| \leq T$. It can be readily appreciated that $t_A = |C_A| + |R_B| + |C_B| + \Delta_{A2} > TL_A + T = TU_A$ with the attack and that $t_A = |C_A| + |R_B| + \Delta_{A1} \approx TL_A < TU_A$ without the attack. Therefore, by checking t_A against Equation (1), the man-in-the-middle attacked can be detected.

20

25

30

Fig. 5 shows a second scenario 500 of a man-in-the-middle attack, where Clark impersonates Alice to Bob. Again the flow diagram is organised in columns: Alice, Clark, and Bob. In step 510, Clark generates z, computes g^z and a key k_C from g^z , and encrypts C'_A – an old statement from Alice. Clark starts the impersonation by sending the ciphertext $e(k_C, C'_A)$ to Bob.

In step 512, upon receipt of the message from Clark, Bob generates y, g^y , and a key k_B from g^y . Bob then speaks a challenge statement C_B , encrypts the challenge statement with k_B , and transmits the ciphertext $e(k_B, C_B)$ to Alice. In step 514, the ciphertext is intercepted by Clark and Clark sends g^z to Bob. In step 516, Bob derives the key k_C from g^z , and decrypts $e(k_C, C'_A)$ with k_C to recover C'_A . Bob listens to the challenge

statement C'_A and believes that C'_A was indeed spoken by Alice. Bob then speaks a response statement R_B , derives a key k_{BC} from g^{zy} , encrypts R_B , transmits the ciphertext $e(k_{BC}, R_B)$ and g^y and starts a clock.

- Next, in step 518, upon interception of the ciphertext e(k_{BC}, R_B) and g^y, Clark derives 5 k_B from g^y and k_{BC} from g^{zy}, and decrypts e(k_B, C_B) to recover C_B. Since Clark is not able to reply to the challenge statement C_B in Alice's voice, Clark encrypts the challenge C_B with k_C and starts a session with Alice by sending e(k_C, C_B) to Alice. In step 520, upon receipt of e(k_C, C_B), Alice generates x, g^x, and a key k_A from g^x. Alice 10 then speaks a challenge statement CA, encrypts the challenge statement with kA, and sends the ciphertext e(k_A, C_A). In step 522, Clark intercepts the ciphertext and sends g^z to Alice. In step 524, Alice derives a key k_{AC} from g^{zx} , and decrypts $e(k_C, C_B)$ to recover C_B. Alice then listens to the challenge statement C_B and believes that she hears Bob's voice. Alice then speaks a response statement R_A, encrypts the response 15 statement with k_{AC} and sends g^x and the ciphertext e(k_{AC}, R_A). In step 526, Clark intercepts the message from Alice and decrypts the ciphertext to obtain the response R_A. Clark then encrypts the response statement with k_{BC} and sends the ciphertext $e(k_{BC}, R_A)$ to Bob.
- In step 528, Bob receives $e(k_{BC}, R_A)$, stops the clock, and decrypts the ciphertext to recover R_A . Without checking the elapsed time of the clock, t_B , Bob can be misled into believing that Bob is communication with Alice since R_A is Alice's reply to the challenge statement C_B . This attack can be foiled easily by checking t_B against the interval (TL_B , TU_B) (see Equation 2), where $TL_B = |C_B| + |R_A|$ and $TU_B = TL_B + T$.
- Without the man-in-the-middle attack by Clark, $t_B = |C_B| + |R_A| + \Delta_{B1}$, where Δ_{B1} is the delay due to processing, transmission, and a pause interval introduced by Alice after listening to C_B but before speaking the response statement R_A . With the man-in-the-middle attack of Fig. 5, $t_B = |C_B| + R_A| + |C_A| + \Delta_{B2}$, where Δ_{B2} is a delay similar to Δ_{B1} . It is required that $T >> \Delta_{B1}$ and Δ_{B2} and that $|C_A| \leq T$. Then it can be seen that $t_B = |C_B| + R_A| + |C_A| + \Delta_{B2} < TL_B + T = TU_B$ with the attack and $t_B = |C_B| + R_A| + \Delta_{B1} \approx$

 $TL_B < TU_B$ without the attack. Therefore, by checking t_B against Equation (2), the man-in-the-middle attack can be detected.

6. Computer Implementation

The embodiments of the invention are preferably implemented using a computer(s), such as the general-purpose computer shown in Fig. 7. In particular, the processes of Figs. 2 and 3 can be implemented as software, or a computer program, executing on the computer, where each communication device 120, 140, 600 of Figs. 1 and 6 can be implemented using a general purpose computer. The method or process steps for remote authentication based on exchanging signals representing biometrics information are effected by instructions in the software that are carried out by the computer. The software may be implemented as one or more modules for implementing the process steps. A module is a part of a computer program that usually performs a particular function or related functions. Also, as described hereinbefore, a module can also be a packaged functional hardware unit for use with other components or modules.

In particular, the software may be stored in a computer readable medium, including the storage devices described below. The software is preferably loaded into the computer from the computer readable medium and then carried out by the computer. A computer program product includes a computer readable medium having such software or a computer program recorded on it that can be carried out by a computer. The use of the computer program product in the computer preferably effects an advantageous apparatus for remote authentication based on exchanging signals representing biometrics information in accordance with the embodiments of the invention.

The computer system 700 consists of the computer 702, a video display 716, and input devices 718, 720. In addition, the computer system 700 can have any of a number of other output devices including line printers, laser printers, plotters, and other reproduction devices connected to the computer 702. The computer system 700 can

be connected to one or more other computers via a communication interface 708b using an appropriate communication channel 730 such as a modem communications path, a computer network, or the like. The computer network may include a local area network (LAN), a wide area network (WAN), an Intranet, and/or the Internet.

5

10

15

20

25

30

The computer 702 itself consists of a central processing unit(s) (simply referred to as a processor hereinafter) 704, a memory 706 which may include random access memory (RAM) and read-only memory (ROM), input/output (IO) interfaces 708A, & 708B a video interface 710, and one or more storage devices generally represented by a block 712 in Fig. 8. The storage device(s) 712 can consist of one or more of the following: a floppy disc, a hard disc drive, a magneto-optical disc drive, CD-ROM, magnetic tape or any other of a number of non-volatile storage devices well known to those skilled in the art. Each of the components 704 to 712 is typically connected to one or more of the other devices via a bus 714 that in turn can consist of data, address, and control buses.

The video interface 710 is connected to the video display 716 and provides video signals from the computer 702 for display on the video display 716. User input to operate the computer 702 can be provided by one or more input devices 708B. For example, an operator can use the keyboard 718 and/or a pointing device such as the mouse 720 to provide input to the computer 702.

The system 700 is simply provided for illustrative purposes and other configurations can be employed without departing from the scope and spirit of the invention. Computers with which the embodiment can be practiced include IBM-PC/ATs or compatibles, one of the Macintosh TM family of PCs, Sun Sparcstation TM, a workstation or the like. The foregoing are merely exemplary of the types of computers with which the embodiments of the invention may be practiced. Typically, the processes of the embodiments, described hereinafter, are resident as software or a program recorded on a hard disk drive (generally depicted as block 712 in Fig. 7) as the computer readable medium, and read and controlled using the processor 704.

Intermediate storage of the program and pixel data and any data fetched from the network may be accomplished using the semiconductor memory 706, possibly in concert with the hard disk drive 712.

In some instances, the program may be supplied to the user encoded on a CD-ROM or a floppy disk (both generally depicted by block 712), or alternatively could be read by the user from the network via a modem device connected to the computer, for example. Still further, the software can also be loaded into the computer system 700 from other computer readable medium including magnetic tape, a ROM or integrated circuit, a magneto-optical disk, a radio or infra-red transmission channel between the computer and another device, a computer readable card such as a PCMCIA card, and the Internet and Intranets including email transmissions and information recorded on websites and the like. The foregoing are merely exemplary of relevant computer readable mediums. Other computer readable mediums may be practiced without departing from the scope and spirit of the invention.

Thus, a method, an apparatus, and a computer program product for remote authentication based on exchanging signals representing biometrics information and establishing a cryptographic key have been described. While only a small number of embodiments are described, it will be apparent to those skilled in the art, in view of this disclosure, that numerous changes and/or modifications can be made without departing from the scope and spirit of the invention.

15

20

25

CLAIMS

- 1. A method of authenticating a remote party and establishing a cryptographic key for secure communications via an insecure communications channel, said method including the steps of:
- generating a first challenge signal of minimum duration T, where T is a fixed time interval;

generating a random number x, computing g^x modulo p, where g and p are numbers, deriving a key k_A from g^x modulo p, encrypting said first challenge signal with k_A and a symmetric key cryptosystem, and sending a first ciphertext to said remote party;

receiving a second ciphertext from said remote party, sending g^x modulo p to said remote party, and starting a clock;

receiving a third ciphertext and g^y modulo p from said remote party, stopping the clock, and computing an elapsed time interval of said clock;

deriving a key k_B from g^y modulo p, computing g^{xy} modulo p, deriving a key k_{AB} from g^{xy} modulo p, decrypting said second ciphertext with k_B to recover a second challenge signal from said remote party, decrypting said third ciphertext to recover a first response signal from said remote party;

verifying that said elapsed time of the clock is within a predetermined interval (TL_A, TU_A), where TL_A and TU_A are positive numbers;

verifying that said second challenge signal is produced by said remote party; producing a second response signal of minimum duration T, encrypting said second response signal with k_{AB} and sending a fourth ciphertext to said remote party;

verifying that said first response signal is a response produced by said remote party to said first challenge signal; and

generating a key k from g^{xy} modulo p for secure communications with said remote party.

2. The method according to claim 1, wherein T is larger than the channel transmission and processing delay.

EXPRESS MAIL LABEL NO.: EL386267783US

- 3. The method according to claim 1, wherein said challenge signals and response signals represent biometrics characteristics of the producing parties.
- 4. The method according to claim 3, wherein said biometrics characteristics include the voice of a person.
 - 5. The method according to claim 1 or 3, wherein verification of said first response signal and said second challenge signal from said remote party is based on familiarity of remote party's biometrics characteristics.

20

25

- 6. The method according to claim 1, wherein encryption of said challenge and response signals is performed using a cryptographic commitment function.
- 7. The method according to claim 1, where TL_A is t₁ + t₂ and TU_A is t₁ +
 t₂ + T, with t₁ being the duration of said first challenge signal and t₂ being the duration of said first response signal.
 - 8. An apparatus for authenticating a remote party and establishing a cryptographic key for secure communications via an insecure communications channel, said apparatus including:

means for generating a first challenge signal of minimum duration T, where T is a fixed time interval;

means for generating a random number x, computing g^x modulo p, where g and p are numbers, deriving a key k_A from g^x modulo p, encrypting said first challenge signal with k_A and a symmetric key cryptosystem, and sending a first ciphertext to said remote party;

means for receiving a second ciphertext from said remote party, sending g^x modulo p to said remote party, and starting a clock;

means for receiving a third ciphertext and g^y modulo p from said remote party, 30 stopping the clock, and computing an elapsed time interval of said clock;

10

15

25

means for deriving a key k_B from g^y modulo p, computing g^{xy} modulo p, deriving a key k_{AB} from g^{xy} modulo p, decrypting said second ciphertext with k_B to recover a second challenge signal from said remote party, decrypting said third ciphertext to recover a first response signal from said remote party;

means for verifying that said elapsed time of the clock is within a predetermined interval (TL_A, TU_A), where TL_A and TU_A are positive numbers;

means for verifying that said second challenge signal is produced by said remote party;

means for producing a second response signal of minimum duration T, encrypting said second response signal with k_{AB} and sending a fourth ciphertext to said remote party;

means for verifying that said first response signal is a response produced by said remote party to said first challenge signal; and

means for generating a key k from g^{xy} modulo p for secure communications with said remote party.

- 9. The apparatus according to claim 8, wherein T is larger than the channel transmission and processing delay.
- 20 10. The apparatus according to claim 8, wherein said challenge signals and response signals represent biometrics characteristics of the producing parties.
 - 11. The apparatus according to claim 10, wherein said biometrics characteristics include the voice of a person.

12. The apparatus according to claim 8 or 10, wherein verification of said first response signal and said second challenge signal from said remote party is based on familiarity of remote party's biometrics characteristics.

20

25

13. The apparatus according to claim 8, wherein encryption of said challenge and response signals is performed using a cryptographic commitment function.

- 5 14. The apparatus according to claim 8, where TL_A is $t_1 + t_2$ and TU_A is $t_1 + t_2 + T$, with t_1 being the duration of said first challenge signal and t_2 being the duration of said first response signal.
- 15. A computer program product having a computer usable medium having a computer readable program code means embodied therein for authenticating a remote party and establishing a cryptographic key for secure communications via an insecure communications channel, said computer program product including:

computer readable program code means for generating a first challenge signal of minimum duration T, where T is a fixed time interval;

computer readable program code means for generating a random number x, computing g^x modulo p, where g and p are numbers, deriving a key k_A from g^x modulo p, encrypting said first challenge signal with k_A and a symmetric key cryptosystem, and sending a first ciphertext to said remote party;

computer readable program code means for receiving a second ciphertext from said remote party, sending g^x modulo p to said remote party, and starting a clock;

computer readable program code means for receiving a third ciphertext and g^y modulo p from said remote party, stopping the clock, and computing an elapsed time interval of said clock;

computer readable program code means for deriving a key k_B from g^y modulo p, computing g^{xy} modulo p, deriving a key k_{AB} from g^{xy} modulo p, decrypting said second ciphertext with k_B to recover a second challenge signal from said remote party, decrypting said third ciphertext to recover a first response signal from said remote party;

computer readable program code means for verifying that said elapsed time of the clock is within a predetermined interval (TL_A, TU_A), where TL_A and TU_A are positive numbers;

computer readable program code means for verifying that said second challenge signal is produced by said remote party;

computer readable program code means for producing a second response signal of minimum duration T, encrypting said second response signal with k_{AB} and sending a fourth ciphertext to said remote party;

computer readable program code means for verifying that said first response signal is a response produced by said remote party to said first challenge signal; and computer readable program code means for generating a key k from g^{xy} modulo p for secure communications with said remote party.

10

5

- 16. The computer program product according to claim 15, wherein T is larger than the channel transmission and processing delay.
- 17. The computer program product according to claim 15, wherein said15 challenge signals and response signals represent biometrics characteristics of the producing parties.
 - 18. The computer program product according to claim 17, wherein said biometrics characteristics include the voice of a person.

- 19. The computer program product according to claim 15 or 17, wherein verification of said first response signal and said second challenge signal from said remote party is based on familiarity of remote party's biometrics characteristics.
- 25 20. The computer program product according to claim 15, wherein encryption of said challenge and response signals is performed using a cryptographic commitment function.
- The computer program product according to claim 15, where TL_A is t₁
 + t₂ and TU_A is t₁ + t₂ + T, with t₁ being the duration of said first challenge signal and t₂ being the duration of said first response signal.

10

15

20

25

22. A method of authenticating a remote party and establishing a cryptographic key for secure communications via an insecure communications channel, said method including the steps of:

receiving a first ciphertext from said remote party, generating a random number y, computing g^y modulo p, where g and p are numbers;

producing a first challenge signal of a minimum duration T, where T is a fixed time interval;

deriving a key k_B from g^y modulo p, encrypting said first challenge signal with k_B and a symmetric key cryptosystem, and sending a second ciphertext to said remote party;

receiving g^x modulo p from said remote party, deriving a key k_A from and g^x modulo p, decrypting said first ciphertext to recover a second challenge signal from said remote party;

verifying that said second challenge signal is produced by said remote party, producing a first response signal of said minimum duration T;

computing g^{xy} modulo p, deriving a key k_{AB} from g^{xy} modulo p, encrypting said first response signal, sending a third ciphertext and g^y modulo p to said remote party, and starting a clock;

receiving a fourth ciphertext, stopping said clock, computing the elapsed time of the clock, and decrypting the fourth ciphertext to recover a second response signal from said remote party;

verifying that said elapsed time of said clock is within a predetermined interval (TL_B, TU_B), where TL_B and TU_B are positive numbers;

verifying that said second response signal is a response produced by said remote party to said first challenge signal; and

generating a key k from g^{xy} modulo p for secure communications with the remote party.

30 23. The method according to claim 22, wherein T is larger than the channel transmission and processing delay

20

25

- 24. The method according to claim 22, wherein said challenge signals and response signals are signals representing biometrics characteristics.
- 5 25. The method according to claim 22, wherein verification of said second challenge signal and said second response signal from remote party is based on familiarity with a remote party's biometrics characteristics.
- 26. The method according to claim 22, wherein encryption of said challenge and response signals is carried out by a cryptographic commitment function.
 - 27. The method according to claim 22, wherein TL_B is $t_3 + t_4$ and TU_B is $t_3 + t_4 + T$, with t_3 being the duration of the first challenge signal and t_4 being the duration of the second response signal.

28. An apparatus for authenticating a remote party and establishing a cryptographic key for secure communications via an insecure communications channel, said apparatus including:

means for receiving a first ciphertext from said remote party, generating a random number y, computing g^y modulo p, where g and p are numbers;

means for producing a first challenge signal of a minimum duration T, where T is a fixed time interval;

means for deriving a key k_B from g^y modulo p, encrypting said first challenge signal with k_B and a symmetric key cryptosystem, and sending a second ciphertext to said remote party;

means for receiving g^x modulo p from said remote party, deriving a key k_A from and g^x modulo p, decrypting said first ciphertext to recover a second challenge signal from said remote party;

means for verifying that said second challenge signal is produced by said remote party, producing a first response signal of said minimum duration T;

10

means for computing g^{xy} modulo p, deriving a key k_{AB} from g^{xy} modulo p, encrypting said first response signal, sending a third ciphertext and g^y modulo p to said remote party, and starting a clock;

means for receiving a fourth ciphertext, stopping said clock, computing the elapsed time of the clock, and decrypting the fourth ciphertext to recover a second response signal from said remote party;

means for verifying that said elapsed time of said clock is within a predetermined interval (TL_B, TU_B), where TL_B and TU_B are positive numbers;

means for verifying that said second response signal is a response produced by said remote party to said first challenge signal; and

means for generating a key k from g^{xy} modulo p for secure communications with the remote party.

- 29. The apparatus according to claim 28, wherein T is larger than the channel transmission and processing delay
 - 30. The apparatus according to claim 28, wherein said challenge signals and response signals are signals representing biometrics characteristics.
- 20 31. The apparatus according to claim 28, wherein verification of said second challenge signal and said second response signal from remote party is based on familiarity with a remote party's biometrics characteristics.
- 32. The apparatus according to claim 28, wherein encryption of said challenge and response signals is carried out by a cryptographic commitment function.
 - 33. The apparatus according to claim 28, wherein TL_B is $t_3 + t_4$ and TU_B is $t_3 + t_4 + T$, with t_3 being the duration of the first challenge signal and t_4 being the duration of the second response signal.

34. A computer program product having a computer usable medium having a computer readable program code means embodied therein for authenticating a remote party and establishing a cryptographic key for secure communications via an insecure communications channel, said computer program product including:

computer readable program code means for receiving a first ciphertext from said remote party, generating a random number y, computing g^y modulo p, where g and p are numbers;

computer readable program code means for producing a first challenge signal of a minimum duration T, where T is a fixed time interval;

computer readable program code means for deriving a key k_B from g^y modulo p, encrypting said first challenge signal with k_B and a symmetric key cryptosystem, and sending a second ciphertext to said remote party;

computer readable program code means for receiving g^x modulo p from said remote party, deriving a key k_A from and g^x modulo p, decrypting said first ciphertext to recover a second challenge signal from said remote party;

computer readable program code means for verifying that said second challenge signal is produced by said remote party, producing a first response signal of said minimum duration T;

computer readable program code means for computing g^{xy} modulo p, deriving a key k_{AB} from g^{xy} modulo p, encrypting said first response signal, sending a third ciphertext and g^y modulo p to said remote party, and starting a clock;

computer readable program code means for receiving a fourth ciphertext, stopping said clock, computing the elapsed time of the clock, and decrypting the fourth ciphertext to recover a second response signal from said remote party;

computer readable program code means for verifying that said elapsed time of said clock is within a predetermined interval (TL_B, TU_B), where TL_B and TU_B are positive numbers;

computer readable program code means for verifying that said second response signal is a response produced by said remote party to said first challenge signal; and

computer readable program code means for generating a key k from g^{xy} modulo p for secure communications with the remote party.

25

30

5

10

15

- 35. The computer program product according to claim 34, wherein T is larger than the channel transmission and processing delay
- 5 36. The computer program product according to claim 34, wherein said challenge signals and response signals are signals representing biometrics characteristics.
- 37. The computer program product according to claim 34, wherein
 10 verification of said second challenge signal and said second response signal from remote party is based on familiarity with a remote party's biometrics characteristics.
 - 38. The computer program product according to claim 34, wherein encryption of said challenge and response signals is carried out by a cryptographic commitment function.
 - 39. The computer program product according to claim 34, wherein TL_B is $t_3 + t_4$ and TU_B is $t_3 + t_4 + T$, with t_3 being the duration of the first challenge signal and t_4 being the duration of the second response signal.

25

15

- 40. A method of authenticating a remote party and establishing a cryptographic key for secure communications via an insecure communications channel, said method including the steps of:
- generating a first challenge signal of minimum duration T, where T is a fixed time interval;

generating a random number x, computing g^x modulo p, where g and p are numbers, deriving a key k_A from g^x modulo p, encrypting said first challenge signal with k_A and a symmetric key cryptosystem, and sending a first ciphertext to said remote party;

receiving a second ciphertext, sending g^x modulo p to said remote party, and starting a clock;

10

15

20

receiving g^y modulo p, computing a key k_B from g^y modulo p, decrypting the second ciphertext to recover a second challenge signal from said remote party;

verifying said second challenge statement to ensure that said second challenge statement is produced by said remote party, and producing a first response signal of minimum duration T;

computing g^{xy} modulo p, deriving a key k_{AB} from g^{xy} modulo p, encrypting said first response signal and sending a third ciphertext to said remote party;

receiving a fourth ciphertext from said remote party, stopping said clock, decrypting the fourth ciphertext with k_{AB} to recover a second response signal from said remote party;

verifying that said elapsed time of said clock is within a predetermined interval (tl_A, tu_A), where tl_A and tu_A are positive numbers;

verifying that said second response signal is a response produced by said remote party to said first challenge signal; and

generating a key k from g^{xy} modulo p for secure communications with said remote party.

- 41. The method according to claim 40, wherein T is larger than the channel transmission and processing delay
- 42. The method according to claim 40, wherein said challenge signals and response signals are signals representing biometrics characteristics.
- 43. The method according to claims 40, wherein verification of said
 25 second response signal and said second challenge signal from remote party is based on
 familiarity of remote party's biometrics characteristics.
 - 44. The method according to claim 40, wherein encryption of said challenge and response signals is carried out by a cryptographic commitment function.

10

15

20

25

30

- 45. The method according to claim 40, where tl_A is $T_1 + T_2$ and tu_A is $T_1 + T_2 + T$, with T_1 being the duration of said first challenge signal and T_2 being the duration of said second response signal.
- 46. An apparatus for authenticating a remote party and establishing a cryptographic key for secure communications via an insecure communications channel, said apparatus including:

means for generating a first challenge signal of minimum duration T, where T is a fixed time interval;

means for generating a random number x, computing g^x modulo p, where g and p are numbers, deriving a key k_A from g^x modulo p, encrypting said first challenge signal with k_A and a symmetric key cryptosystem, and sending a first ciphertext to said remote party;

means for receiving a second ciphertext, sending g^x modulo p to said remote party, and starting a clock;

means for receiving g^y modulo p, computing a key k_B from g^y modulo p, decrypting the second ciphertext to recover a second challenge signal from said remote party;

means for verifying said second challenge statement to ensure that said second challenge statement is produced by said remote party, and producing a first response signal of minimum duration T;

means for computing g^{xy} modulo p, deriving a key k_{AB} from g^{xy} modulo p, encrypting said first response signal and sending a third ciphertext to said remote party;

means for receiving a fourth ciphertext from said remote party, stopping said clock, decrypting the fourth ciphertext with k_{AB} to recover a second response signal from said remote party;

means for verifying that said elapsed time of said clock is within a predetermined interval (tl_A , tu_A), where tl_A and tu_A are positive numbers;

means for verifying that said second response signal is a response produced by said remote party to said first challenge signal; and

means for generating a key k from g^{xy} modulo p for secure communications with said remote party.

- 47. The apparatus according to claim 46, wherein T is larger than the channel transmission and processing delay
 - 48. The apparatus according to claim 46, wherein said challenge signals and response signals are signals representing biometrics characteristics.
- 10 49. The apparatus according to claims 46, wherein verification of said second response signal and said second challenge signal from remote party is based on familiarity of remote party's biometrics characteristics.
- 50. The apparatus according to claim 46, wherein encryption of said challenge and response signals is carried out by a cryptographic commitment function.
 - 51. The apparatus according to claim 46, where tl_A is $T_1 + T_2$ and tu_A is $T_1 + T_2 + T$, with T_1 being the duration of said first challenge signal and T_2 being the duration of said second response signal.

20

30

- 52. A computer program product having a computer usable medium having a computer readable program code means embodied therein for authenticating a remote party and establishing a cryptographic key for secure communications via an insecure communications channel, said computer program product including:
- computer readable program code means for generating a first challenge signal of minimum duration T, where T is a fixed time interval;

computer readable program code means for generating a random number x, computing g^x modulo p, where g and p are numbers, deriving a key k_A from g^x modulo p, encrypting said first challenge signal with k_A and a symmetric key cryptosystem, and sending a first ciphertext to said remote party;

10

15

20

25

computer readable program code means for receiving a second ciphertext, sending g^x modulo p to said remote party, and starting a clock;

computer readable program code means for receiving g^y modulo p, computing a key k_B from g^y modulo p, decrypting the second ciphertext to recover a second challenge signal from said remote party;

computer readable program code means for verifying said second challenge statement to ensure that said second challenge statement is produced by said remote party, and producing a first response signal of minimum duration T;

computer readable program code means for computing g^{xy} modulo p, deriving a key k_{AB} from g^{xy} modulo p, encrypting said first response signal and sending a third ciphertext to said remote party;

computer readable program code means for receiving a fourth ciphertext from said remote party, stopping said clock, decrypting the fourth ciphertext with k_{AB} to recover a second response signal from said remote party;

computer readable program code means for verifying that said elapsed time of said clock is within a predetermined interval (tl_A, tu_A), where tl_A and tu_A are positive numbers;

computer readable program code means for verifying that said second response signal is a response produced by said remote party to said first challenge signal; and computer readable program code means for generating a key k from g^{xy} modulo p for secure communications with said remote party.

- 53. The computer program product according to claim 52, wherein T is larger than the channel transmission and processing delay
- 54. The computer program product according to claim 52, wherein said challenge signals and response signals are signals representing biometrics characteristics.

- 55. The computer program product according to claims 52, wherein verification of said second response signal and said second challenge signal from remote party is based on familiarity of remote party's biometrics characteristics.
- 5 56. The computer program product according to claim 52, wherein encryption of said challenge and response signals is carried out by a cryptographic commitment function.
- 57. The computer program product according to claim 52, where tl_A is T_1 + 10 T_2 and tu_A is $T_1 + T_2 + T$, with T_1 being the duration of said first challenge signal and T₂ being the duration of said second response signal.
 - A method of authenticating a remote party and establishing a 58. cryptographic key for secure communications via an insecure communications channel, said method including the steps of:

receiving a first ciphertext from remote party, generating a random number y, and computing gy modulo p, where g and p are numbers;

producing a first challenge signal of minimum duration T, where T is a fixed time interval;

deriving a key k_B from g^y modulo p, encrypting said first challenge signal with k_B and a symmetric key cryptosystem, and sending a second ciphertext;

receiving gx modulo p, computing a key kA from gx modulo p, decrypting said first ciphertext to recover a second challenge signal from remote party, sending gy to remote party and starting a clock;

verifying said second challenge statement to make sure that said second challenge statement is produced by said remote party, and then producing a first response signal of minimum duration T;

computing g^{xy} modulo p, deriving a key k_{AB} from g^{xy} modulo p, encrypting said first response signal and sending a third ciphertext to said remote party;

20

25

receiving a fourth ciphertext from said remote party, stopping said clock, decrypting said fourth ciphertext with k_{AB} to recover a second response signal from said remote party;

verifying that said elapsed time of the clock is within an interval (tl_B , tu_B), where tl_B and tu_B are positive numbers;

verifying that said second response signal a response produced by said remote party to said first challenge signal; and

generating a key k from g^{xy} modulo p for secure communications with the remote party.

10

5

- 59. The method according to claim 58, wherein T is larger than the channel transmission and processing delay
- 60. The method according to claim 58, wherein said challenge signals and response signals are signals representing biometrics characteristics.
 - 61. The method according to claim 58, wherein verification of said second challenge signal and said second response signal from said remote party is based on familiarity of said remote party's biometrics characteristics.

20

- 62. The method according to claim 58, wherein encryption of challenge and response signals are carried out by a cryptographic commitment function.
- The method according to claim 58, where tl_B is T₃ + T₄ and tu_B is T₃ +
 T₄ + T, with T₃ being the duration of said first challenge signal and T₄ being said duration of said second response signal.
 - 64. An apparatus for authenticating a remote party and establishing a cryptographic key for secure communications via an insecure communications channel, said apparatus:

means for receiving a first ciphertext from remote party, generating a random number y, and computing g^y modulo p, where g and p are numbers;

means for producing a first challenge signal of minimum duration T, where T is a fixed time interval;

means for deriving a key k_B from g^y modulo p, encrypting said first challenge signal with k_B and a symmetric key cryptosystem, and sending a second ciphertext;

means for receiving g^x modulo p, computing a key k_A from g^x modulo p, decrypting said first ciphertext to recover a second challenge signal from remote party, sending g^y to remote party and starting a clock;

means for verifying said second challenge statement to make sure that said second challenge statement is produced by said remote party, and then producing a first response signal of minimum duration T;

means for computing g^{xy} modulo p, deriving a key k_{AB} from g^{xy} modulo p, encrypting said first response signal and sending a third ciphertext to said remote party;

means for receiving a fourth ciphertext from said remote party, stopping said clock, decrypting said fourth ciphertext with k_{AB} to recover a second response signal from said remote party;

means for verifying that said elapsed time of the clock is within an interval (tl_B, tu_B) , where tl_B and tu_B are positive numbers;

means for verifying that said second response signal a response produced by said remote party to said first challenge signal; and

means for generating a key k from g^{xy} modulo p for secure communications with the remote party.

- 65. The apparatus according to claim 64, wherein T is larger than the channel transmission and processing delay
- 66. The apparatus according to claim 64, wherein said challenge signals and response signals are signals representing biometrics characteristics.

25

5

10

15

15

20

25

- 67. The apparatus according to claim 64, wherein verification of said second challenge signal and said second response signal from said remote party is based on familiarity of said remote party's biometrics characteristics.
- 5 67. The apparatus according to claim 64, wherein encryption of challenge and response signals are carried out by a cryptographic commitment function.
 - 68. The apparatus according to claim 64, where tl_B is $T_3 + T_4$ and tu_B is $T_3 + T_4 + T$, with T_3 being the duration of said first challenge signal and T_4 being said duration of said second response signal.
 - 69. A computer program product having a computer usable medium having a computer readable program code means embodied therein for authenticating a remote party and establishing a cryptographic key for secure communications via an insecure communications channel, said computer program product:

computer readable program code means for receiving a first ciphertext from remote party, generating a random number y, and computing g^y modulo p, where g and p are numbers;

computer readable program code means for producing a first challenge signal of minimum duration T, where T is a fixed time interval;

computer readable program code means for deriving a key k_B from g^y modulo p, encrypting said first challenge signal with k_B and a symmetric key cryptosystem, and sending a second ciphertext;

computer readable program code means for receiving g^x modulo p, computing a key k_A from g^x modulo p, decrypting said first ciphertext to recover a second challenge signal from remote party, sending g^y to remote party and starting a clock;

computer readable program code means for verifying said second challenge statement to make sure that said second challenge statement is produced by said remote party, and then producing a first response signal of minimum duration T; computer readable program code means for computing g^{xy} modulo p, deriving a key k_{AB} from g^{xy} modulo p, encrypting said first response signal and sending a third ciphertext to said remote party;

computer readable program code means for receiving a fourth ciphertext from said remote party, stopping said clock, decrypting said fourth ciphertext with k_{AB} to recover a second response signal from said remote party;

computer readable program code means for verifying that said elapsed time of the clock is within an interval (tl_B, tu_B), where tl_B and tu_B are positive numbers;

computer readable program code means for verifying that said second response signal a response produced by said remote party to said first challenge signal; and computer readable program code means for generating a key k from g^{xy} modulo p for secure communications with the remote party.

- 70. The computer program product according to claim 69, wherein T is larger than the channel transmission and processing delay
 - 71. The computer program product according to claim 69, wherein said challenge signals and response signals are signals representing biometrics characteristics.

20

15

5

72. The computer program product according to claim 69, wherein verification of said second challenge signal and said second response signal from said remote party is based on familiarity with said remote party's biometrics characteristics.

25

73. The computer program product according to claim 69, wherein encryption of challenge and response signals are carried out by a cryptographic commitment function.

74. The computer program product according to claim 69, where tl_B is $T_3 + T_4$ and tu_B is $T_3 + T_4 + T$, with T_3 being the duration of said first challenge signal and T_4 being said duration of said second response signal.

-47-

REMOTE AUTHENTICATION BASED ON EXCHANGING SIGNALS REPRESENTING BIOMETRICS INFORMATION

5 ABSTRACT

A method, an apparatus, and a computer program product for remote authentication are disclosed. The methods are based on exchanging of signals representing remote party's biometrics information (such as acoustic waveforms) and have application in secure telephony or video-conferencing communications over open networks. The apparatus includes a speech encoding/decoding module (632), a control module (636), an encryption/decryption module (640), a key generator (650), a Diffie Hellman key exchange system (660), a timer module (670) for measuring time between a challenged statement and a corresponding response statement, an input/output (I/O) module (680) for transmitting and receiving data via a communications channel 610.

15 FIG. 6

10




FIG. 1




FIG. 2




FIG. 3




FIG. 4





FIG. 5






FIG. 7

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION FOR UTILITY OR
DESIGN
PATENT APPLICATION
(37 CFR 1.63)

As a below named inventor, I hereby declare that:

Declaration Submitted with Initial Filing

the specification of which

Declaration OR Submitted after Initial Filing (surcharge (37 ČFR 1.16 (e))

required)

Attorney Docket Number			1
First Named Invento	r	WU, Yongdong	
COMPLI	ETE II	KNOWN	
Application Number		/	
Filing Date			_
Group Art Unit			
Examiner Name			

My residence, post office address, and citizenship are as stated below next to my name. I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: REMOTE AUTHENTICATION BASED ON EXCHANGING SIGNALS REPRESENTING BIOMETRICS INFORMATION

- V		(Tide Of the filveridon)	
♣ J	is attached hereto OR		
	was filed on (MM/DD/YYYY)	as United States Application Number or PCT Intern	national
Applica	ation Number	and was amended on (MM/DD/YYYY) (if app	licable)
	by state that I have reviewed and ded by any amendment specifical	understand the contents of the above identified specification, including the claims, as y referred to above.	

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

					
Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Co	opy Attached? NO
9906598-8	SINGAPORE	12/24/1999	0000	0000	数ロロロ

		y data sheet PTO/SB/02B	

hereby claim the benefit under 35	U.S.C. 119(e) of any United States provisio	nal application(s) listed below.
Application Number(s)	Filing Date (MM/DD/YYYY)	
		Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

EXPRESS MAIL LABEL NO.: EL386267783US

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DE	CL	.AF	AS	TI	O	Ν
----	----	-----	----	----	---	---

ADDITIONAL INVENTOR(S) Supplemental Sheet Page ___ of ___

Name of Additional Joint Inventor, if any: A petition has been filed for this unsigned inventor							ventor			
Given Na	me (first and middle [if an	yl)				Family Na	me or S	Sumame)	
Huijie, Ro	bert			DE	NG					
inventor's Signature	R.De	~ <u>~</u>						Date	,	24/2/00
Residence: City		State			Country	Singapo	re	Citizen	- 1	Singapore
Post Office Address	2 Namly Rise			•			***			
Post Office Address										
City	Singapore	State			ZIP 2	267110	Country	, Sir	ngap	ore
Name of Addition	nal Joint Inventor, if a	ny:			A petition	on has been file	ed for th	is unsig	ned in	ventor
Given Na	me (first and middle [if any	/])				Family Na	me or S	umame	!	
Feng BAO										
Inventor's Signature	US (bu							ıtę	24/2/0
Residence: City	Singapore	State			Country	Singapo	re	Citize	nship	China
Post Office Address	37, West Coast I	Park, #0	04-06	, Pa	rk Vie	w Condo	· · · · · ·			
Post Office Address										:
City	Singapore	State			ZIP	127653	Coun	try	Sin	gapore
Name of Additior	nal Joint Inventor, if a	ny:			A petitio	on has been file	d for thi	s unsigi	ned inv	/ento r
Given Nar	me (first and middle [if any	<u>(</u>])				Family Nar	me or S	umame		
Inventor's Signature			1					Da	te	
Residence: City	State Country Citizenship									
Post Office Address										
Post Office Address					Υ	T				
City		State			ZIP		Co	ountry		

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

PTO/SB/01 (12-97)
Approved for use through 9/10/01 10/83/81/2032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION — Utility or Design Patent Application

										_		
United States of United States of information white	of Americ r PCT In ch is ma	fit under 35 U.S.(ca, listed below a ternational applic terial to patental international filin	and, inse ation in oility as	ofar as the sub the manner pro defined in 37 C	ject matter vided by th FR 1.56 w	of eac	ch of the	e claims of th	is applicat	ion is	not disclosed	in the prior
		ent Applicati Numb	on or					ling Date	F		nt Patent I	
		Hamb	<u> </u>					<i>,</i> ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			., uppiou	
Additional	U.S. or F	CT international	applicat	tion numbers ar	e listed on	a supp	lementa	I priority data	sheet PTC)/SB/0	2B attached h	nereto.
		ereby appoint the				s) to pro	osecute	this application	on and to ti	ansac		
and trademark	Office co	nnected therewit	n: 📙	Customer Num OR	ber						Place Cust Number Bar	
				Registered pra		name/r	registrati	ion number lis	ted below			
	Nam	<u>e</u>			ration nber			Nam	ie			stration mber
Additional re	egistered	d practitioner(s) n	amed o	n supplemental	Registered	Practi	itioner Ir	nformation she	et PTO/SI	3/02C	attached here	eto.
Direct all corre	esponde			er Number Code Label				OR	Cor	espo	ndence add	ress below
Name		·										
Address					<u> </u>							
Address												
City						St	ate		ZIP			
Country				Telephor	re				Fax			
believed to be to punishable by f	true; and ine or in	I statements mad d further that the aprisonment, or t issued thereon.	se state both, ur	ements were m	nade with th	he kno	wiedge	that willful fa	lse statem	ents a	and the like s	o made are
Name of So	le or F	irst Invento	r:]_				petitio	n has been	filed for t	his u	nsigned inve	entor
Giv	en Nar	ne (first and mi	ddle [if	anvl)				Family	v Name o	r Sur	name	
Yongdo	ong					W	U					
Inventor's Signature		Wn	Y.	njdonj		·	.—				Date	24/02/2000
Residence: C	ity	Singapor	е	State		C	ountry	Singap	ore	_	Citizenship	China
Post Office Ad	idress	10, Ghim	Moh	Road, #1	3-80				<u> </u>			
Post Office Ad	ddress											_
City		Singapore	State		ZIP	27	0010		Count	ry	Singapo	ore
	invento	rs are being na	med o	n the <u>1</u> su	pplementa	al Add	itional I	Inventor(s)	sheet(s) F	PTO/S	SB/02A attac	ched heret

Approved for use through 6/30/99. OMB 0651-0035

Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

POWER OF ATTORNEY OR AUTHORIZATION OF AGENT, NOT ACCOMPANYING APPLICATION

Application Number		
Filing Date		
First Named Inventor	WU, Yongdong	
Group Art Unit		
Examiner Name		
Attorney Docket Number		

I hereby appoint:							
Practitioners at 0	Customer Number			Place Customer Number Bar Code Label here			
X Practitioner(s) r	named below:						
	Name			on Number			
JOSEPH	H. HANDLEMAN		26179				
JOHN R	ICHARDS		31053				
RICHAR	D J. STREIT		25765				
JULIAN	H. COHEN		20302				
	(s) or agent(s) to prosecute the applic ent and Trademark Office connected			ve, and to transact all			
Please change the	correspondence address for the above	ve-iden	tified applica	ition to:			
The above-men	tioned Customer Number.						
OR							
X Firm or Individual Name	LADAS & PARRY						
Address	26 WEST 61ST STREET						
Address							
City	NEW YORK	State	NY	7IP 10023			
Country	UNITED STATES OF AMERIC						
Telephone	(212) 708-1800	Fax	(212) 2	246-8959			
I am the: Applicant.							
, , ,	of record of the entire interest under 37 CFR 3.73(b) is enclosed						
	SIGNATURE of Applicant or Assig	nee of	Record				
Name WU,	Yongdong						
Signature	Wa Yongdonf						
Date							

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Approved for use through 6/30/99. OMB 0651-0035
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays

a valid OMB control number.

POWER OF ATTORNEY OR AUTHORIZATION OF AGENT, NOT ACCOMPANYING APPLICATION

Application Number		
Filing Date		
First Named Inventor	WU, Yongdong	
Group Art Unit		
Examiner Name		
Attorney Docket Number		

I hereby appoint:									
Practition OR	ners at (Place Customer Number Bar Code Label here						
X Practitioner(s) named below:									
		Name	Registration	tion Number					
J	JOSEPH H. HANDLEMAN			26179					
J	JOHN RICHARDS			31053	3				
	RICHARD J. STREIT			25765					
J	ULIAN	H. COHEN		20302					
as my/our attorney(s) or agent(s) to prosecute the application identified above, and to transact all business in the Patent and Trademark Office connected therewith.									
Please change the correspondence address for the above-identified application to: The above-mentioned Customer Number. OR									
X Firm <i>or</i> Individua	Firm or LADAS & PARRY								
Address		26 WEST 61ST STREET							
Address			•						
City		NEW YORK	State	NY	ZIP 100	023			
Country		UNITED STATES OF AMERIC							
Telephone		(212) 708-1800	Fax	(212) 2	212) 246-8959				
I am the: Applicant.									
Assignee of record of the entire interest Certificate under 37 CFR 3.73(b) is enclosed									
		SIGNATURE of Applicant or Assig	nee of l	Record					
Name	DENG, Huijie, Robert								
Signature	R	. No							
Date	2	4/2/00	-						

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Approved for use through 6/30/99. OMB 0651-0035

Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

POWER OF ATTORNEY OR AUTHORIZATION OF AGENT, NOT ACCOMPANYING APPLICATION

Application Number		
Filing Date		
First Named Inventor	WU, Yongdong	
Group Art Unit		
Examiner Name		
Attorney Docket Number		

I hereby appoint:									
Practitioners at Customer Number OR X Practitioner(s) named below: Place Customer Number Bar Code Label here									
Name			Registration Number						
JOSEPH H. HANDLEMAN			26179						
JOHN RICHARDS			31053						
RICHARD J. STREIT			25765						
JULIAN	H. COHEN		20302						
as my/our attorney(s) or agent(s) to prosecute the application identified above, and to transact all business in the Patent and Trademark Office connected therewith.									
Please change the correspondence address for the above-identified application to: The above-mentioned Customer Number. OR									
X Firm or LADAS & PARRY									
Address									
Address									
City	NEW YORK	State	NY	ZIP 1	.0023				
Country	UNITED STATES OF AMERICA								
Telephone	(212) 708-1800	Fax	(212) 2	246-8959					
I am the: X Applicant.									
Assignee of record of the entire interest Certificate under 37 CFR 3.73(b) is enclosed									
SIGNATURE of Applicant or Assignee of Record									
Name BAC	BAO, Feng								
Signature	1~8 Bu								
Date	24/02/00								

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.